



Cactus® Double Coated Film Tape

Technical Data Sheet No. K2970

Product Information

Cactus® Double Coated Film Tape K2970 is an acrylic solvent-based pressure sensitive adhesive tape which offers 2 adhesion levels on both sides, open side is coated with higher adhesion providing quick bonding result, ideal for a wide variety of substrates where high adhesion level is required.

Composition & Physical Properties

Adhesive System	: Solvent Acrylic	Tape Thickness	: 3.0 mil (0.075 ± 0.005 mm)						
Carrier	: 1/2 mil PET	Tack J. Dow No.	: <table border="1"> <thead> <tr> <th></th> <th>Open Side</th> <th>Closed Side</th> </tr> </thead> <tbody> <tr> <td></td> <td>18</td> <td>14</td> </tr> </tbody> </table>		Open Side	Closed Side		18	14
	Open Side	Closed Side							
	18	14							
Liner Thickness	: 3 mil	Peel Adhesion PSTC-1	: <table border="1"> <tbody> <tr> <td>49.4 oz/inch (1.4kg / 25mm)</td> <td>28.2 oz/inch (0.8kg / 25mm)</td> </tr> </tbody> </table>	49.4 oz/inch (1.4kg / 25mm)	28.2 oz/inch (0.8kg / 25mm)				
49.4 oz/inch (1.4kg / 25mm)	28.2 oz/inch (0.8kg / 25mm)								
Liner Material	: Glassine Paper	Shear Strength PSTC-7	: Over 24 hrs with 35.3 oz loading on 1" x 1" (1.0 kg / 25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)						
Liner Density	: #60 (90 g/m ²)	Service Temperature	: -4°F ~ 248°F (-20°C ~ 120°C)						
Liner Color	: White	Tape Color	: Clear						

Applications

- For laminating porous surfaces such as foam, sandpaper, etc.
- Temporary fixing of billboards, nameplates and emblems

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.