

Product Information

Cactus® Double Coated Film Tape W2970 is an acrylic solvent-based pressure sensitive adhesive tape which offers high shear holding power and initial tack for quick bonding results.

Composition & Physical Properties

Adhesive System	1:	Solvent Acrylic	Tape Thickness :	5 mil (0.13 ± 0.005mm)
Carrier	:	1/2 mil PET Film	Tack :	J. Dow No. 14
Liner Thickness	:	3 mil	Loop Tack :	77 oz/inch (2.2 kg / 25mm)
Liner Material	:	Glassine Paper	Peel Adhesion PSTC-3	63 oz/inch (over 1.8 kg / 25 mm)
Liner Density	:	#60 (90 g/m²)	Shear Strength PSTC-7	Over 24 hrs with 1 kg loading on 25mm x 25mm
Liner Color	:	White	Service Temperature :	-22°F ~ 248°F (-30°C ~ 120°C)
			Tape Color :	Clear

Applications

- Various industrial splicing and mounting applications.
- · Adhering golf or tennis grips to golf shafts or tennis handles
- Fixing of nameplates, Point of Purchase displays, signs, labels and emblems

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.

Copyright $\ensuremath{\textcircled{O}}$ 2020 V. Himark (USA) Inc., all rights reserved.

www.cactustape.com